CHEMICAL COATED TWIST BOPET FILM

PROVISIONAL

PRODUCT DESCRIPTION

Chiripal Poly Films CPW71 is biaxially oriented transparent polyester film with inside Antistatic coating and outside Corona Treated. The corona treated side is suitable for printing. This film is also available with outside coating and inside Corona treated

FEATURES

- Good clarity and transperancy
- Good adhesion to inks
- Excellent twistability and dead
- fold retention ability Suitable for high speed candy machine

APPLICATION

- Twist wrap for chocolate, lollipop, etc.
- ▶Gift wrapping

PROPERTIES		UNIT	TEST METHOD	CP15W71	CP18W71	CP23W71
Nominal Thickness		Micron	Internal	15	18	23
		Gauge	Method	60	72	92
Yield		m²/kg	-	47.6	39.7	31.1
MECHANICAL PROPE	ERTIES (Mi	n)				
Tensile Strength	MD		ASTM	2400	2400	2400
	TD	kg/cm ²	D-882	2500	2500	2500
Elongation Break	MD		ASTM	100	100	100
	TD	%	D-882	90	90	90
THERMAL PROPERT	IES					
Thermal	MD			25	25	25
Shrinkage		%	ASTM			
(at 150°C /30 mins)	TD		D-1204	30	30	30
SURFACE PROPERTI	ES (Max)					
COF	Static		ASTM	0.35	0.35	0.35
(Film to film)	Dynamic	-	D-1894	0.30	0.30	0.30
SURFACE TENSION						
Coated Side	-	Dyne/cm	ASTM D 2578	48	48	48
Corona Treated side	-	Dyne/cm	ASTM D 2578	54	54	54
OPTICAL PROPERTIE	S					
Haze (max.)		%	ASTM D-1003	3.5	4.0	4.5
Light Transmission		%	ASTM D-1003	88	88	88
OTHER PROPERTIES						
Twist Ability			Internal			
Dead Fold Ability		-	Method	Excellent	Excellent	Excellent
BARRIER PROPERTII	ES					
WVTR (37.7°C, 90% RH)		gm/m²	ASTM F-	40	40	40
		/day	1249			
02 Permeability (23°C, 0%RH)		cm³/m²	ASTM D-			
		/day	3985-95	130	130	130

Note: MD – Machine Direction, TD – Transverse Direction, COF - Co-efficient of Friction

DISCLAIMER: The property given in the present technical data sheet does not constitute product specification but represents typical performance values based on the best of our knowledge and believed to be accurate. These are given in good faith, and the Customer is requested to satisfy its suitability for its particular purpose. The user is solely responsible for the end-use of the product and needs to perform tests to confirm the product suitability/compatibility in all respects. Chiripal Poly Films does not guarantee typical values and reserves the right to change the technical datasheet anytime required to enhance the quality of the products without prior information.