



CORONA TREATED BOPET FILM

PRODUCT DESCRIPTION

Chiripal Poly Films CPT10 is Biaxially Oriented Transparent Polyester film with one side corona and other side plain. The corona side is suitable for Printing or lamination

FEATURES

- Excellent stiffness & mechanical properties.
- Excellent transparency and surface properties
- Corona side enhances the ink and metal adhesion
- Excellent machine ability & dimensional stability over a wide range of temperature.

APPLICATION

- Packaging (food and non- food) application
- Carton lamination with solvent based inks system
- ▶ Metallizing application

PROPERTIES		UNIT	TEST METHOD	CP23T10	CP36T10	CP40T10	CP50T10
Nominal Thickness		Micron	Internal	23	36	40	50
		Gauge	Method	92	144	160	200
Yield		m²/kg		31.1	19.8	17.8	14.2
MECHANICAL PROP	ERTIES (Mi	n)					
Tensile Strength	MD		ASTM	2200	1900	1900	1900
	TD	kg/cm ²	D-882	2100	1800	1800	1800
Elongation Break	MD		ASTM	110	110	110	110
	TD	%	D-882	100	100	100	100
THERMAL PROPERT	IES (Max)						
Thermal	MD			2.4	2.4	2.4	2.4
Shrinkage		%	ASTM				
(at 150°C /30 mins)	TD		D-1204	0.4	0.4	0.4	0.4
SURFACE PROPERT	IES (Max)						
COF	Static		ASTM	0.48	0.48	0.48	0.48
(Film to Film)	Dynamic	-	D-1894	0.42	0.42	0.42	0.42
SURFACE TENSION						·	
Plain Side			ASTM	44	44	44	44
		Dyne/cm	D-2578				
Corona Treated Side				54	54	54	54
OPTICAL PROPERTII	ES						
Haze (Max)			ASTM	4.0	4.5	5.0	5.5
		%	D-1003				
Light Transmission			ASTM	88	88	88	88
			D-1003				
BARRIER PROPERTI	ES					·	
WVTR, 37.7°C, 90% RH		gm/m²	ASTM F-1249	40	40	40	40
		/day					
02 Permeability 23°C, 0%RH		cm³/m²	ASTM D-				
		/day	3985-95	130	130	130	130

Note: MD - Machine Direction, TD - Transverse Direction, COF - Co-efficient of Friction

DISCLAIMER: The property given in the present technical data sheet does not constitute product specification but represents typical performance values based on the best of our knowledge and believed to be accurate. These are given in good faith, and the Customer is requested to satisfy its suitability for its particular purpose. The user is solely responsible for the end-use of the product and needs to perform tests to confirm the product suitability/compatibility in all respects. Chiripal Poly Films does not guarantee typical values and reserves the right to change the technical datasheet anytime required to enhance the quality of the products without prior information.