



# CPFL-FBR

## FILM GRADE BRIGHT POLYESTER CHIPS

### PRODUCT FEATURES AND APPLICATION

CPFL-FBR is film grade bright polyester chips. It is suitable for manufacturing polyester films for flexible packaging and industrial applications.

TEST PARAMETERS		UNIT	TEST METHOD	TYPICAL VALUE
Intrinsic Viscosity		dl/gm	Phenol : DCB (60:40) @ 25 °C	0.63±0.01
End Group (COOH)		Meq/kg	CPQA/WI/32	≤35
DEG		Wt%	CPQA/WI/52	1.1±0.1
Melting Point		Deg C	CPQA/WI/36	256±2
Color	L	Hunter	CPQA/WI/37	≥ 58
	b	Hunter	CPQA/WI/37	≤ 8
Ash		%	CPQA/WI/38	<0.03
Moisture content (When packed)		%	CPQA/WI/41	<0.25
Chip/gm		Nos	CPQA/WI/50	30±5

### FOOD CONTACT

CPF-BR complies with EC and FDA regulations.

### STORAGE & HANDLING

Reccomended to store at temperature below 30 °C & humidity 55±5 %

### DISCLAIMER

The property given in this technical data sheet do not constitute product specifications but represent typical performance values based on the best of our knowledge and believed to be accurate. These are given in good faith but it is for the customer to satisfy of the suitability for its own particular purpose. The user is solely responsible for the end use of the product and needs to perform their own tests to confirm the product suitability/compatibility in all respects. Chiripal Polyfilm does not guarantee the typical values and reserves the right to change the technical data sheet at any time for enhancing the quality of the products without prior information.



Corporate Office: Chiripal House Shivranjani Cross Road Satellite, Ahmedabad-380015 India  
www.chiripalpolyfilms.in petresin.marketing@chiripalgroup.com